

# ELULED



# ELULED


Emergency Luminaires  
LED Emergency Twinspot

## General Specifications

Application	Anti-Panic Lighting, Escape Route lighting, Hazardous Area Lighting
Mounting	Direct mounting to wall & ceiling
Version	Manual Test, Self Test, DALI
Mode	Non-maintained
Emergency Duration	1/3/8 hours
Light Source	2x25 mid power led spot, 4000-6500K, CRI>80
Battery	Ni-Cd, Ni-MH, VRLA (Sealed Lead Acid Battery)
Wiring	Up to 2x2,5 mm <sup>2</sup> quick fit terminal block
Power Supply	230 Volt, 50/60Hz
Protection	IP65
Temperature Range	0-45°C, VRLA 0-25°C
Electrical Class	Class II (no earth wiring required)
Material	Thermoplastic housing



## Dimensions (mm)



## Ordering Details

Code	Type	Duration	Light Output	Battery			
ELULED-345-1H	ECO	1 hour	2 x 515 Lumen	3.6V, 4.5Ah Ni-Cd			
ELULED-445-1H			2 x 685 Lumen	4.8V, 4.5Ah Ni-Cd			
ELULED-645-1H			2 x 765 Lumen	7.2V, 4.5Ah Ni-Cd			
ELULED-345-3H		3 hours	8 hours	2 x 220 Lumen	3.6V, 4.5Ah Ni-Cd		
ELULED-445-3H				2 x 300 Lumen	4.8V, 4.5Ah Ni-Cd		
ELULED-645-3H				2 x 430 Lumen	7.2V, 4.5Ah Ni-Cd		
ELULED-1207-3H				2 x 750 Lumen	12V, 7Ah VRLA		
ELULED-645-8H				2 x 175 Lumen	7.2V, 4.5Ah Ni-Cd		
ELULED-1207-8H				2 x 280 Lumen	12V, 7Ah VRLA		
ELULED-340-1H-ST	SELF TEST	1 hour	2 x 450 Lumen	3.6V, 4.0Ah Ni-MH			
ELULED-345-1H-ST			2 x 515 Lumen	3.6V, 4.5Ah Ni-Cd			
ELULED-440-1H-ST			2 x 610 Lumen	4.8V, 4.0Ah Ni-MH			
ELULED-445-1H-ST			2 x 685 Lumen	4.8V, 4.5Ah Ni-Cd			
ELULED-645-1H-ST			2 x 765 Lumen	7.2V, 4.5Ah Ni-Cd			
ELULED-340-3H-ST			3 hours	8 hours	2 x 200 Lumen	3.6V, 4.0Ah Ni-MH	
ELULED-345-3H-ST		2 x 220 Lumen			3.6V, 4.5Ah Ni-Cd		
ELULED-440-3H-ST		2 x 255 Lumen			4.8V, 4.0Ah Ni-MH		
ELULED-445-3H-ST		2 x 300 Lumen			4.8V, 4.5Ah Ni-Cd		
ELULED-640-3H-ST		2 x 390 Lumen			7.2V, 4.0Ah Ni-MH		
ELULED-645-3H-ST		2 x 430 Lumen			7.2V, 4.5Ah Ni-Cd		
ELULED-1207-3H-ST		2 x 750 Lumen			12V, 7Ah VRLA		
ELULED-340-3H-DALI		DALI			3 hours	2 x 200 Lumen	3.6V, 4.0Ah Ni-MH
ELULED-345-3H-DALI						2 x 220 Lumen	3.6V, 4.5Ah Ni-Cd
ELULED-440-3H-DALI						2 x 255 Lumen	4.8V, 4.0Ah Ni-MH
ELULED-445-3H-DALI						2 x 300 Lumen	4.8V, 4.5Ah Ni-Cd
ELULED-640-3H-DALI						2 x 390 Lumen	7.2V, 4.0Ah Ni-MH
ELULED-645-3H-DALI			2 x 430 Lumen	7.2V, 4.5Ah Ni-Cd			
ELULED-1207-3H-DALI			2 x 750 Lumen	12V, 7Ah VRLA			