

## Practilite PCL SERIES

Surface Mounted, Single/Double Sided



### General Specifications

- Aluminium (silver anodized) enclosure
- Fire retardant ABS "Quick Connect Part"
- Double Sided with screen printed, laser engraved or "easy change" sign plate
- PCLZNC, PCLBRK, PCLANK and PCLQC (quick connect) versions
- Designed for indoor use
- LED light source
- Wall mounted with bracket/quick connect part
- Ceiling mounted with bracket/steel wire/chain/recessed or quick connect part
- Standalone Self-Test available
- Manufactured to comply with EN60598-2-22

### Technical Specifications

System Mode	: Maintained; Centrally Powered
Input Voltage	: - 230V; 50/60Hz (self contained) - 24V or 230V AC/DC (centrally powered)
Light Source	: LED Strip
Charging Indicator	: Green LED
Battery	: High temp Ni-MH, polarised cable connector
Emergency Duration	: 3 hours (for self contained models)
Insulation Class	: Class I
Protection Class	: IP30
Temperature	: 0 - 40°C
Enclosure / Color	: Aluminium (anodized) / Silver
Side Covers / Color	: ABS / Dark Gray
Viewing Distance	: 24m

### Ordering Details

Product Code	Model	Mounting Detail	Light Source	Operating Mode	Duration	
PCLZNC-M310	Standard	Chain/Wire (2x25cm)	10xLED 60 Lumen	M Maintained	3 hours	
PCLBRK-M310		Bracket				
PCLANK-M310		Recessed				
PCLQC-M310		Quick Connect Part				
PCLZNC-M310-ST	Chain/Wire (2x25cm)					
PCLBRK-M310-ST	Bracket					
PCLANK-M310-ST	Recessed					
PCLQC-M310-ST	Quick Connect Part					
PCLZNC-1024	Central	Chain/Wire (2x25cm)		24V AC/DC	Central	
PCLBRK-1024		Bracket				
PCLANK-1024		Recessed				
PCLQC-1024		Quick Connect Part				
PCLZNC-10230		Chain/Wire (2x25cm)	230V AC/DC			
PCLBRK-10230		Bracket				
PCLANK-10230		Recessed				
PCLQC-10230		Quick Connect Part				
PLX-UTL-S	Screen Printed Perspex Slab					
PLX-UTL-P	Laser Engraved Perspex Slab					
PLX-PCL-TRAM	Trammed Perspex Slab with Easy Change Sign Sheets (2 pcs)					

### Dimensions (mm)

